RICHMOND ROBOTICS


APEX C1500-L

Smart, Reliable, Safe.


Apex C1500-L is the most versatile autonomous forklift that works together with other AMRs and automation equipment; is compatible with GMA and Euro pallets; and covers end-to-end pallet movement, pallet stacking, high shelf receiving and putaway for payloads up to 1,500 kg. This product has been passed CE-MD ISO3691-4 certification.




REFERENCE



SAFETY COVERAGE



DRIVING SURFACE



TURNING REFERENCE

PRODUCT SPECIFICATION



APEX C1500-L

Dimensions	Length	2,495 mm (82.22 in)
	Width	1,250 mm (49.21 in)
	Height	2,190 mm (86.22 in)
	Turning Diameter	3,020 mm (II8.89 in)
Dayland	Weight	
Payload	Max. Payload	1,500 kg (3,306 lbs)
	- I axi i ayioaa	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Function	Configuration	Yes
	Fork Dimensions	1,160/122/40 mm
		(45.66/4.80/1.57 in)
	Fork Carriage Width	680/560/460 mm
		(26.77/22.04/18.11 in)
	Default Fork Height	40 mm (1.57 in)
	Max. Fork Height	3,000 mm (II8.II in)-1,500 kg (3,306 lbs)
	(Customizable)	4,500 mm (177.16 in)-600 kg (1,322 lbs)
	Load Center	500 mm (19.68 in)
	Pallet Compatibility	Euro Pallets, GMA Pallets, Customized Pallets*
Performance	Navigation Mode	Natural / Preferred Route / Hybrid
	Positioning Mode	Laser SLAM / Visual Semantics / Optional QR Code Navigation
Communication	Wi-Fi (IEEE 802.11a/b/g/nac)	Yes
	Wi-Fi (IEEE 802.11ax)	Optional
	Cellular Network (Public 4G/5G)	Optional
Power	Endurance	~8 hrs Per Charge
	Battery Type	LFP
Sensors	LiDAR	5
	3D Cameras	
	Pallet in-Place Sensor	2
	Pallet off-Place Sensor	2
Safety	Safety Bumper	Yes
	Emergency Stop Button	2
Compliance	CE	Yes